PRODUCT RECOMMENDATION

HARLEY-DAVIDSON TOURING FLH/FLT/FLR FLHTC/I ELECTRA GLIDE CLASSIC (2005-2006)

ENGINE Twin Cam 88
Capacity: 3,8 liter

USE		CLIMATE
Normal (alternative)		Moderate
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		

Change every 8000 km

USE		CLIMATE
Normal (preferred)		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		

Change every 8000 km

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		

Change every 1600 km

USE		CLIMATE
Acceptable		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Bi-Turbo 15W-40	**Bi-Turbo 20W-50**	

PRIMARY CHAINDRIVE

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		

Change every 16000 km

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

HARLEY-DAVIDSON TOURING FLH/FLT/FLR FLHTC/I ELECTRA GLIDE CLASSIC (2005-2006)

TRANSMISSION 5
Capacity: 0,59-0,71 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		

Change every 32000 km

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		

Change every 1600 km

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	

Check every 8000 km, change every 24 months

FRONT FORK
Capacity: 0,32 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367