

# HARLEY-DAVIDSON TOURING

## FLH/FLT/FLR FLHTCU ULTRA CLASSIC

### ELECTRA GLIDE SHRINE FLM (2011-2013)



**ENGINE** Twin Cam 103  
Capacity: 3,79 liter

| USE                | CLIMATE       |
|--------------------|---------------|
| Normal (preferred) | Mediterranean |

PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50**

*Change every 8000 km*

| USE             | CLIMATE       |
|-----------------|---------------|
| Initial service | Mediterranean |

PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50**

*Change every 1600 km*

| USE            | CLIMATE       |
|----------------|---------------|
| Short distance | Mediterranean |

PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50**

*Change every 2400 km*

**PRIMARY CHAINDRIVE**  
Capacity: 1,32 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50**

*Change every 16000 km*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50**

*Change every 1600 km*

# HARLEY-DAVIDSON TOURING FLH/FLT/FLR FLHTCU ULTRA CLASSIC ELECTRA GLIDE SHRINE FLM (2011-2013)

**TRANSMISSION 6**

Capacity: 0,95 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 32000 km*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 1600 km***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4***Check every 8000 km, change every 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.