HARLEY-DAVIDSON TOURING FLH/FLT/FLR FLTR/I ROAD GLIDE (2005-2006)

ENGINE Twin Cam 88 Capacity: 3,8 liter		
USE		**CLIMATE**
Normal (alternative)		Moderate
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 8000 km		
USE		**CLIMATE**
Normal (preferred)		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 8000 km		
USE		**CLIMATE**
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 1600 km		
USE		**CLIMATE**
Acceptable		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Bi-Turbo 15W-40	**Bi-Turbo 20W-50**	

PRIMARY CHAINDRIVE		
USE		**CLIMATE**
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 16000 km		

HARLEY-DAVIDSON TOURING FLH/FLT/FLR FLTR/I ROAD GLIDE (2005-2006)

TRANSMISSION 5
Capacity: 0,59-0,71 liter

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		

Change every 32000 km

USE		CLIMATE
Initial service		Moderate

PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		

Change every 1600 km

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	

Check every 8000 km, change every 24 months

FRONT FORK
Capacity: 0,32 liter

We are unable to give a standard recommendation for this component. Please contact our service department.