

# HARLEY-DAVIDSON VRSC VRS VRSCB V-ROD (2003-2005)



## ENGINE/TRANSMISSION Revolution

Capacity: 4,3 liter, Capacity: 4,7 liter (Overhaul capacity)

USE	CLIMATE
Normal	Mediterranean

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 8000 km*

USE	CLIMATE
Initial service	Mediterranean

## PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 1600 km*

## HYDRAULIC BRAKE SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

## HYDRAULIC CLUTCH SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

## COOLING SYSTEM

Capacity: 2,4 liter

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

## PRODUCT RECOMMENDATION 2

**Coolant SP 12***Change every 48000 km*

USE	CLIMATE
Initial service	Moderate

## PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

## PRODUCT RECOMMENDATION 2

**Coolant SP 12***Change every 1600 km*

## FRONT FORK

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.