HARLEY-DAVIDSON WL WLC (1941-1944)



ENGINE Flathead W Capacity: 4,25 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Monograde 50		
Change every 1600 km		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Classic Monograde 30		
Change every 1600 km		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
HDX 10W		
Change every 1600 km		
TRANSMISSION 3 Capacity: 2,85 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Monograde 50		
Check every 400 km, change every 1600	km	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Classic Monograde 30		
Check every 400 km, change every 1600	km	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
HDX 10W		
Check every 400 km, change every 1600	km	

HARLEY-DAVIDSON WL WLC (1941-1944)



GENERATOR COMMUTATOR END BEARING				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2			
Change eveny 10000 km	<u> </u>	<u> </u>		

Change every 10000 km

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	Multi Purpose Grease 3

Change every 400 km

STEERING HEAD BEARINGS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	
Change every 80000 km		

WHEEL BEARINGS			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		
Change every 800 km	·	·	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.