

# HERKULES CONQUEST ATV 600 4X4

## CONQUEST (2011-2013)

**ENGINE**

Capacity: 3 liter (Dry fill), Capacity: 2,7 liter (Service fill), Filter capacity: 0,3 liter

## USE

Normal

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Expulsa RR 15W-50***Change every 1000 km/ 3 months*

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-40**

## PRODUCT RECOMMENDATION 2

**Expulsa RR 10W-40**

## PRODUCT RECOMMENDATION 3

**Expulsa 10W-40***Change every 1000 km/ 3 months*

## USE

Initial service

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Expulsa RR 15W-50***Change every 300 km*

## USE

Initial service

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-40**

## PRODUCT RECOMMENDATION 2

**Expulsa RR 10W-40**

## PRODUCT RECOMMENDATION 3

**Expulsa 10W-40***Change every 300 km***DIFFERENTIAL FRONT**

Capacity: 0,15 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 5015**

## PRODUCT RECOMMENDATION 2

**Gearlube GL-4 80W**

## PRODUCT RECOMMENDATION 3

**Gearlube GL-4 80W-90***Change every 4000 km/ 12 months*

## USE

Initial service

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 5015**

## PRODUCT RECOMMENDATION 2

**Gearlube GL-4 80W**

## PRODUCT RECOMMENDATION 3

**Gearlube GL-4 80W-90***Change every 300 km*

# HERKULES CONQUEST ATV 600 4X4

## CONQUEST (2011-2013)



### GEARBOX REAR HIGH/LOW 2/1

Capacity: 0,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 5015</b>	<b>Gearlube GL-4 80W</b>	<b>Gearlube GL-4 80W-90</b>

*Change every 4000 km/ 12 months*

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 5015</b>	<b>Gearlube GL-4 80W</b>	<b>Gearlube GL-4 80W-90</b>

*Change every 300 km*

### HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

*Change every 4000 km/ 12 months*

### COOLING SYSTEM

Capacity: 2,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Check every 500 km, change every 4000 km/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.