HONDA GL GOLD WING GL 1800 GOLD WING (2006-2017)



ENGINE/TRANSMISSION Capacity: 3,7 liter, Capacity: 4,6 liter (Overhaul capacity), Filter capacity: 0,1 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Expulsa 10W-40				
Change every 12000 km/ 12 months				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1				
Expulsa 10W-40				
Change even 1000 km				

Change every 1000 km

FINAL REDUCTION Capacity: 0,12 liter, Capacity: 0,15 liter (Overhaul capacity)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 5015	SP Gear 1071		
Check every 12000 km/ 12 months, change every 36000 km/ 36 months			

HYDRAULIC BRAKE SYSTEM USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2

Drauliquid-LV Super DOT 4 Drauliquid-S DOT 4

Check every 6000 km/ 6 months, change every 18000 km/ 24 months

HYDRAULIC CLUTCH SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

Check every 6000 km/ 6 months, change every 18000 km/ 24 months

HONDA GL GOLD WING GL 1800 GOLD WING (2006-2017)



COOLING SYSTEM					
Capacity: 3,85 liter (Radiator + engine), Capacity: 0,65 liter (Reserve tank)					
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2				
Coolant -38 Organic NF	Coolant -26				

Check every 12000 km/ 12 months, change every 36000 km/ 24 months

FRONT FORK Capacity: 0,53 liter (Left), Capacity: 0,48 liter (Right)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Fork Oil RR 10				
Check every 12000 km/ 12 months				

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.