

HONDA RVF RVF 750 R (1993-1995)**ENGINE/TRANSMISSION**

Capacity: 3,7 liter, Filter capacity: 0,1 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Tropical |

PRODUCT RECOMMENDATION 1

HDX 40*Change every 12000 km/ 12 months*

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

Expulsa RR 15W-50

PRODUCT RECOMMENDATION 2

HDX 15W-40

PRODUCT RECOMMENDATION 3

HDX 20W-50*Change every 12000 km/ 12 months*

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Expulsa RR 10W-40

PRODUCT RECOMMENDATION 2

Expulsa 10W-40

PRODUCT RECOMMENDATION 3

HDX 10W-40*Change every 12000 km/ 12 months*

| USE | CLIMATE |
|--------|---------|
| Normal | Arctic |

PRODUCT RECOMMENDATION 1

HDX 10W*Change every 12000 km/ 12 months***HYDRAULIC BRAKE SYSTEM**

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Check every 6000 km/ 6 months, change every 18000 km/ 24 months***HYDRAULIC CLUTCH SYSTEM**

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Check every 6000 km/ 6 months, change every 18000 km/ 24 months*

HONDA RVF RVF 750 R (1993-1995)**GREASE POINTS/NIPPLES**

| USE | | CLIMATE |
|---------------------------------|------------------------------|-------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 | Multi Purpose Grease 3 |

Check every 12000 km/ 12 months

COOLING SYSTEM

Capacity: 2,8 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

Check every 12000 km/ 12 months, change every 36000 km/ 24 months

FRONT FORK

Capacity: 0,45 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| ATF Dexron II-D | | |

Check every 12000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.