## **HONDA VFR VFR 1200X CROSSTOURER DCT** (2012-2019)



| ENGINE/TRANSMISSION Capacity: 4,9 liter (Dry fill), Capacity: 3,9-4 liter (Service fill), Filter capacity: 0,3-0,4 liter |  |          |  |  |
|--|--|----------|--|--|
| USE  |  | CLIMATE  |  |  |
| Normal   |  | Moderate |  |  |
| PRODUCT RECOMMENDATION 1   |  |          |  |  |
| Expulsa 10W-40   |  |          |  |  |
| Change every 12000 km  |  |          |  |  |
| USE  |  | CLIMATE  |  |  |
| Initial service  |  | Moderate |  |  |
| PRODUCT RECOMMENDATION 1   |  |          |  |  |
| Expulsa 10W-40   |  |          |  |  |
| Change every 1000 km   |  |          |  |  |

| SHAFT DRIVE Capacity: 0,24 liter (Dry fill), Capacity: 0,2 liter (Service fill) |                          |          |  |  |
|---|--------------------------|----------|--|--|
| USE   |                          | CLIMATE  |  |  |
| Normal  |                          | Moderate |  |  |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 |          |  |  |
| SP Gear 5015  | SP Gear 1071             |          |  |  |
| Change every 24 months  |                          | ,        |  |  |

| HYDRAULIC BRAKE SYSTEM ABS Capacity: 0-0 liter (Between min and max.) |                          |          |  |
|---|--------------------------|----------|--|
| USE   |                          | CLIMATE  |  |
| Normal  |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 |          |  |
| Drauliquid-LV Super DOT 4   | Drauliquid-S DOT 4       |          |  |
| Change every 24 months  | '                        | ,        |  |

| HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.) |                          |          |  |  |
|--|--------------------------|----------|--|--|
| USE  |                          | CLIMATE  |  |  |
| Normal   |                          | Moderate |  |  |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2 |          |  |  |
| Drauliquid-LV Super DOT 4  | Drauliquid-S DOT 4       |          |  |  |
| Change every 24 months   |                          |          |  |  |

PRODUCT RECOMMENDATION

## HONDA VFR VFR 1200X CROSSTOURER DCT (2012-2019)



| COOLING SYSTEM Capacity: 3,7-3,94 liter |          |
|---|----------|
| USE                                     | CLIMATE  |
| Normal                                  | Moderate |
| PRODUCT RECOMMENDATION 1                |          |
| Coolant SP 11                           |          |
| Change every 36 months                  |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.