HUSQVARNA TE TE 125 (2011-2013)



ENGINE/TRANSMISSION Capacity: 1,15 liter, Filter capacity: 0,2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Expulsa RR 5W-50			
Change every 3000 km			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1			
Expulsa RR 5W-50			
Change every 1000 km			

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Check every 6000 km, change every 1	2 months	'	

01 1 10001		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Initial service		Moderate
USE		CLIMATE

Check every 1000 km

COOLING SYSTEM Capacity: 1,2 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

HUSQVARNA TE TE 125 (2011-2013)



FRONT FORK	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Fork Oil RR 5	
Change every 9000 km	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.