

HUSQVARNA WR WR 250 (2010-2013)**ENGINE**

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION 5

Capacity: 0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 10W-40

Change every 3000 km

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 10W-40

Change every 1000 km

USE	CLIMATE
Competition	Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 10W-40

Change every 8 hours

USE	CLIMATE
Competition, first service only	Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 10W-40

Change every 4 hours

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Change every 10000 km

USE	CLIMATE
Competition	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Check every 4 hours, change every 40 hours

HUSQVARNA WR WR 250 (2010-2013)**COOLING SYSTEM**

Capacity: 1,1-1,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 1500 km

USE		CLIMATE
Competition		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

*Check every 4 hours***FRONT FORK**

We are unable to give a standard recommendation for this component. Please contact our service department.

SHOCK ABSORBER REAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Fork Oil RR 5		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.