

HYOSUNG GT GT 250 COMET (2003-2004)**ENGINE/TRANSMISSION**

Capacity: 1,65 liter (Dry fill), Capacity: 1,5 liter (Service fill), Filter capacity: 0,5 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Bi-Turbo 20W-50***Change every 4000 km***USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Expulsa RR 5W-50****PRODUCT RECOMMENDATION 2****Expulsa RR 15W-50****PRODUCT RECOMMENDATION 3****Expulsa RR 10W-40***Change every 4000 km***USE**

Initial service

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Bi-Turbo 20W-50***Change every 1000 km***USE**

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Expulsa RR 5W-50****PRODUCT RECOMMENDATION 2****Expulsa RR 15W-50****PRODUCT RECOMMENDATION 3****Expulsa RR 10W-40***Change every 1000 km***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4***Change every 24 months***FRONT FORK**

Capacity: 400 CM3 (each leg)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Fork Oil RR 5***Check every 4000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

HYOSUNG GT GT 250 COMET (2003-2004)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.