

INDIAN CHIEF/VINTAGE CHIEF BOMBER (2010-2011)



ENGINE 105
Capacity: 3,31 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 15W-50

PRODUCT RECOMMENDATION 2

Bi-Turbo 20W-50

Change every 8000 km

USE
Initial service

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 15W-50

PRODUCT RECOMMENDATION 2

Bi-Turbo 20W-50

Change every 800 km

USE
Second change only

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 15W-50

PRODUCT RECOMMENDATION 2

Bi-Turbo 20W-50

Change every 4000 km

PRIMARY DRIVE
Capacity: 0,59-0,65 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Change every 8000 km

USE
Initial service

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Change every 800 km

INDIAN CHIEF/VINTAGE CHIEF BOMBER (2010-2011)



TRANSMISSION 6
Capacity: 0,6-0,72 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Unigear HS GL-3/GL-5 80W-90

Change every 8000 km

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Unigear HS GL-3/GL-5 80W-90

Change every 800 km

HYDRAULIC BRAKE SYSTEM FRONT
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4

Change every 16000 km/ 24 months

HYDRAULIC BRAKE SYSTEM REAR
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4

Change every 16000 km/ 24 months

HYDRAULIC CLUTCH SYSTEM
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4

Change every 16000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.