KAWASAKI KAF/KAT/KDF (MULE) MULE 3020 KAF 620F (2001-2003)



ENGINE Capacity: 1,8 liter, Filter capacity: 0,3 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40		
Change every 5000 km/ 250 hours/ 12 months				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40		

Change every 1000 km/ 50 hours		
TRANSFERBOX Capacity: 2,2 liter		
use Normal		climate Mediterranean
PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	Mediterraneari
Change every 10000 km/ 500 hours/	12 months	
use Normal		climate Cold
PRODUCT RECOMMENDATION 1 SP Gear 5015	PRODUCT RECOMMENDATION 2 SP Gear 1071	
Change every 10000 km/ 500 hours/	12 months	'
use Initial service		climate Mediterranean
PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	
Change every 1000 km/ 50 hours		'
use Initial service		climate Cold
PRODUCT RECOMMENDATION 1 SP Gear 5015	PRODUCT RECOMMENDATION 2 SP Gear 1071	
Change every 1000 km/ 50 hours	1	1

KAWASAKI KAF/KAT/KDF (MULE) MULE 3020 KAF 620F (2001-2003)



HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
Drauliquid DOT 3			
Check every 5000 km/ 250 hours, change every 24 months			

COOLING SYSTEM Capacity: 4,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 24 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.