

# KAWASAKI KLX KLX 250S KLX250-TC (2012-2017)



## ENGINE/TRANSMISSION

Capacity: 1,3 liter (Dry fill), Capacity: 1,1 liter (Service fill), Filter capacity: 0,1 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|--------------------------|
| <b>Expulsa RR 5W-50</b>  | <b>Expulsa RR 15W-50</b> | <b>Expulsa RR 5W-40</b>  |

*Change every 12000 km/ 12 months*

| USE             | CLIMATE       |
|-----------------|---------------|
| Initial service | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|--------------------------|
| <b>Expulsa RR 5W-50</b>  | <b>Expulsa RR 15W-50</b> | <b>Expulsa RR 5W-40</b>  |

*Change every 1000 km*

## HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
|----------------------------------|---------------------------|--------------------------|
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> | <b>Drauliquid DOT 3</b>  |

*Change every 24000 km/ 24 months*

## COOLING SYSTEM

Capacity: 1,3 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1      |  |  |
|-------------------------------|--|--|
| <b>Coolant -38 Organic NF</b> |  |  |

*Change every 36000 km/ 36 months*

## FRONT FORK

Capacity: 531 CM3 (each side, dry fill), Capacity: 450 CM3 (each side, service fill)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Fork Oil RR 5</b>     |  |  |

*Check every 12000 km/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.