KAWASAKI KRF (TERYX) TERYX 800 KRF800 AE>FN/JN (2014 AND AFTER)



ENGINE/TRANSMISSION Capacity: 4 liter (Dry fill), Capacity: 3,6 liter (Service fill), Filter capacity: 0,2 liter				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40		
Change every 6 months	·			
USE		CLIMATE		
Normal		Arctic		
PRODUCT RECOMMENDATION 1				
Expulsa RR 5W-40				
Change every 6 months				
USE		CLIMATE		
Initial service		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40		
Change every 200 km/ 20 hours	·			
USE		CLIMATE		
Initial service		Arctic		
PRODUCT RECOMMENDATION 1				
Expulsa RR 5W-40				
Change every 200 km/20 hours	•			

KAWASAKI KRF (TERYX) TERYX 800 KRF800 AE>FN/JN (2014 AND AFTER)



DIFFERENTIAL FRONT Capacity: 0,92 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 12 months		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	SP Gear 1071	
Change every 12 months		
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 200 km/ 20 hours		
USE		CLIMATE
Initial service		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	SP Gear 1071	
Change every 200 km/ 20 hours		

DIFFERENTIAL REAR

Capacity: 0,98 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Change every 24 months	

PRODUCT RECOMMENDATION

KAWASAKI KRF (TERYX) TERYX 800 KRF800 AE>FN/JN (2014 AND AFTER)



COOLING SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		
Change every 24 months	·	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.