

# KAWASAKI NINJA ZX-6 ZX600 / ZX636

## NINJA ZX-6RR ZX600-N1 (2005-2005)

**ENGINE/TRANSMISSION**

Capacity: 3,6 liter, Capacity: 4 liter (Overhaul capacity), Filter capacity: 0,2 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Expulsa RR 5W-50</b>	<b>Expulsa RR 15W-50</b>	<b>Expulsa RR 5W-40</b>

*Change every 12000 km/ 12 months*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Expulsa RR 5W-50</b>	<b>Expulsa RR 15W-50</b>	<b>Expulsa RR 5W-40</b>

*Change every 1000 km***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

*Check every 6000 km/ 1 months, change every 24000 km/ 24 months***COOLING SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Coolant -38 Organic NF</b>		

*Change every 24000 km/ 24 months***FRONT FORK**

Capacity: 428-432 CM3 (each leg)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.