

KAWASAKI Z SERIES ZR / ZX Z 650-C3

(1979-1979)



ENGINE/TRANSMISSION

Capacity: 3,5 liter, Filter capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40

Change every 5000 km/ 12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40

Change every 800 km

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 5000 km/ 1 months, change every 10000 km/ 12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 800 km

GREASE POINTS/NIPPLES GENERAL

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HDX 30		

Change every 5000 km

KAWASAKI Z SERIES ZR / ZX Z 650-C3

(1979-1979)

**FRONT FORK**

Capacity: 186-194 CM3 (each side)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Change every 10000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.