

KAWASAKI Z SERIES ZR / ZX Z 750 ZR750 - L7F/M7F > LA/MA (2007-2010)



ENGINE/TRANSMISSION

Capacity: 3,8 liter (Dry fill), Capacity: 3,3 liter (Service fill), Filter capacity: 0,2 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 5W-40

Change every 12000 km/ 12 months

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 5W-40

Change every 1000 km

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 24000 km/ 24 months

COOLING SYSTEM

Capacity: 2,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Change every 36000 km/ 36 months

FRONT FORK

Capacity: 481-489 CM3 (Left fork leg, dry fill), Capacity: 410 CM3 (Left fork leg, service fill), Capacity: 465-473 CM3 (Right fork leg, dry fill), Capacity: 400 CM3 (Right fork leg, service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Fork Oil RR 5		

Check every 12000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.