PRODUCT RECOMMENDATION

KINROAD XT150 XT150T-17



| ENGINE Capacity: 0,9 liter (Dry fill), Capacity: 0,75 liter (Service fill) | | | |
|---|--------------------------|--------------------------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Expulsa RR 10W-40 | Expulsa 10W-40 | HDX 10W-40 | |
| Change every 1000 km | | | |
| USE | | CLIMATE | |
| Initial service | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Expulsa RR 10W-40 | Expulsa 10W-40 | HDX 10W-40 | |
| Change every 300 km | | | |

Change every 300 km

| FINAL GEAR Capacity: 0,11 liter | | |
|------------------------------------|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-4 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Change every 5000 km | | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |

Change every 300 km

Gearlube GL-4 80W-90

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Unigear HS GL-3/GL-5 80W-90