

# KTM 1190 ADVENTURE 1190 ADVENTURE (EDS) (2015-2015)



## ENGINE/TRANSMISSION

Capacity: 3,6 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-50***Change every 15000 km/ 12 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-40***Change every 15000 km/ 12 months*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-50***Change every 1000 km*

USE	CLIMATE
Initial service	Arctic

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-40***Change every 1000 km*

## HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 5.1**

PRODUCT RECOMMENDATION 2

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 3

**Drauliquid-S DOT 4***Change every 24 months*

## HYDRAULIC CLUTCH SYSTEM

Capacity: 0-0 liter (Between min and max.)

We are unable to give a standard recommendation for this component. Please contact our service department.

# KTM 1190 ADVENTURE 1190 ADVENTURE (EDS) (2015-2015)

**COOLING SYSTEM**

Capacity: 2,4 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Coolant SP 15+****PRODUCT RECOMMENDATION 2****Coolant SP 12***Change every 48 months***FRONT FORK WP 4860 MXTA SPLIT EDS**

Capacity: 675 CM3 (each leg)

We are unable to give a standard recommendation for this component. Please contact our service department.

**SHOCK ABSORBER REAR WP 4614 WAD EDS**

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*