KTM 200 200 EXC (2004-2009)



ENGINE		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Tornado	Maestrol	

TRANSMISSION 6	
Capacity: 0,7 liter use	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Expulsa RR 15W-50	
Change every 4000 km/ 12 months/ 40 ho	urs
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Expulsa RR 15W-50	
Change every 1000 km/ 10 hours	
USE	CLIMATE
Competition	Moderate
PRODUCT RECOMMENDATION 1	
Expulsa RR 15W-50	
Change every 1 race	'

Capacity. 0-0 liter (Between min and max	·)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 5.1		
Change every 12 months/ 40 hours		
USE		CLIMATE
Competition		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 5.1		

HYDRAULIC BRAKE SYSTEM

KTM 200 200 EXC (2004-2009)



HYDRAULIC CLUTCH SYSTEM

Capacity: 0-0 liter (Between min and max.)

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM Capacity: 1,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

FRONT FORK		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Fork Oil RR 5		
Change every 4000 km/ 12 months/ 40 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.