

**ENGINE**

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Tornado**

## PRODUCT RECOMMENDATION 2

**Maestrol****TRANSMISSION 6**

Capacity: 0,7 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Expulsa RR 15W-50***Change every 20 hours***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Drauliquid DOT 5.1**

## PRODUCT RECOMMENDATION 2

**Drauliquid-LV Super DOT 4**

## PRODUCT RECOMMENDATION 3

**Drauliquid-S DOT 4***Change every 12 months***HYDRAULIC CLUTCH SYSTEM**

Capacity: 0-0 liter (Between min and max.)

We are unable to give a standard recommendation for this component. Please contact our service department.

**COOLING SYSTEM**

Capacity: 1,2 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF***Check every 20 hours***FRONT FORK WP 4860 MXMA PA**

Capacity: 620 CM3 (each leg)

We are unable to give a standard recommendation for this component. Please contact our service department.

**SHOCK ABSORBER REAR WP PDS 5018 DCC**

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or*

# KTM 200 200 EXC (2013-2014)



*inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*