## **KTM 200 200 MXC** (2003-2003)



ENGINE	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Tornado	

TRANSMISSION 6 Capacity: 0,7 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Expulsa RR 10W-40			
Change every 4000 km/ 12 months/ 40 hours			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1			
Expulsa RR 10W-40			
Change every 1000 km/ 10 hours			

HYDRAULIC BRAKE SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 5.1		
Change every 12 months	·	

## **HYDRAULIC CLUTCH SYSTEM**

Capacity: 0-0 liter (Between min and max.)

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM Capacity: 1,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 4000 km/ 12 months		

7602 EC Almelo

## KTM 200 200 MXC (2003-2003)



FRONT FORK Capacity: 830-840 CM3		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Fork Oil RR 5		
Change every 4000 km/ 12 months/ 40 hours		

Change every 4000 km/ 12 months/ 40 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.