KTM 250 250 SX-F (2015-2015)



| ENGINE/TRANSMISSION Capacity: 1,1 liter | | |
|---|--------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Expulsa RR 5W-50 | | |
| Change every 10 hours/ 70 liter consumed | d fuel | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Expulsa RR 5W-50 | | |
| Change every 1 hours/ 7 liter consumed fu | iel | |

| HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.) | | | | |
|---|---------------------------|--------------------------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | | |
| Drauliquid DOT 5.1 | Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | | |
| Change every 12 months | | | | |

| HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max | .) | |
|--|---------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Drauliquid DOT 5.1 | Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 |
| Change every 12 months | | |

| COOLING SYSTEM Capacity: 0,95 liter | | | |
|-------------------------------------|--------------------------|---------------------|--|
| use Normal | | climate Moderate | |
| | | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Coolant SP 15+ | Coolant SP 12 | | |

FRONT FORK WP 4860 MXMA CC Capacity: 195 CM3 (cartridge each), Capacity: 400 CM3 (each leg without cartridge)

We are unable to give a standard recommendation for this component. Please contact our service department.

PRODUCT RECOMMENDATION

KTM 250 250 SX-F (2015-2015)



SHOCK ABSORBER REAR WP 5018 BAVP DCC

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.