PRODUCT RECOMMENDATION

KTM 250 250 SX (2015-2015)

ENGINE

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Tornado	**Maestrol**	

TRANSMISSION 6

Capacity: 0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Expulsa RR 15W-50		

Change every 20 hours/ 140 liter consumed fuel

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid DOT 5.1	**Drauliquid-LV Super DOT 4**	**Drauliquid-S DOT 4**

Change every 12 months

HYDRAULIC CLUTCH SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid DOT 5.1	**Drauliquid-LV Super DOT 4**	**Drauliquid-S DOT 4**

Change every 12 months

COOLING SYSTEM

Capacity: 1,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	**Coolant SP 12**	

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

KTM 250 250 SX (2015-2015)

FRONT FORK WP 4860 MXMA CC
Capacity: 195 CM3 (cartridge each), Capacity: 400 CM3 (each leg without cartridge)

We are unable to give a standard recommendation for this component. Please contact our service department.

SHOCK ABSORBER REAR WP 5018 BAVP DCC

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367