KTM 250 250 XCF-W (USA) (2007-2010)



ENGINE/TRANSMISSION Capacity: 1,1 liter				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1				
Expulsa RR 5W-50				
Change every 10 hours/ 70 liter consumed fuel				
USE		CLIMATE		
Normal		Cold		
PRODUCT RECOMMENDATION 1				
Expulsa RR 5W-40				
Change every 10 hours/ 70 liter consumed fuel				
USE		CLIMATE		
Initial service		Mediterranean		
PRODUCT RECOMMENDATION 1				
Expulsa RR 5W-50				
Change every 3 hours/ 20 liter consumed fuel				
USE		CLIMATE		
Initial service		Cold		
PRODUCT RECOMMENDATION 1				
Expulsa RR 5W-40				
Change every 3 hours/ 20 liter consumed fuel				

Drauliquid DOT 5.1	Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4
Drouliquid DOT 5 1	Drauliquid LV Super DOT 4	Drauliquid S DOT 4
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
Capacity: 0-0 liter (Between min and m	ax.)	

Change every 12 months

HYDRAULIC CLUTCH SYSTEM Brembo				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Drauliquid DOT 5.1	Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

Change every 12 months

KTM 250 250 XCF-W (USA) (2007-2010)



COOLING SYSTEM Capacity: 1,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

FRONT FORK Capacity: 195 CM3 (cartridge each), Capacity: 360-375 CM3 (each leg without cartridge) USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 Fork Oil RR 5 Change every 10 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.