

KTM 300 300 EXC (2004-2009)**ENGINE**

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Tornado | Maestrol | |

TRANSMISSION 6

Capacity: 0,8 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Expulsa RR 15W-50 | | |

Change every 4000 km/ 12 months/ 40 hours

| USE | | CLIMATE |
|--------------------------|--|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Expulsa RR 15W-50 | | |

Change every 1000 km/ 10 hours

| USE | | CLIMATE |
|--------------------------|--|----------|
| Competition | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Expulsa RR 15W-50 | | |

*Change every 1 race***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

| USE | | CLIMATE |
|---------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Drauliquid DOT 5.1 | | |

Change every 12 months/ 40 hours

| USE | | CLIMATE |
|---------------------------|--|----------|
| Competition | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Drauliquid DOT 5.1 | | |

Change every 12 months/ 20 hours

KTM 300 300 EXC (2004-2009)**HYDRAULIC CLUTCH SYSTEM**

Capacity: 0-0 liter (Between min and max.)

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM

Capacity: 1,3 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

FRONT FORK

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Fork Oil RR 5 | | |

Change every 4000 km/ 12 months/ 40 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.