PRODUCT RECOMMENDATION

# KTM 450 450 SX-F (2013-2015)

## ENGINE/TRANSMISSION
Capacity: 1,5 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Expulsa RR 5W-50** | | |

*Change every 10 hours/ 70 liter consumed fuel/ each race*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Expulsa RR 5W-50** | | |

*Change every 1 hours/ 7 liter consumed fuel*

## HYDRAULIC BRAKE SYSTEM
Capacity: 0-0 liter (Between min and max.)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Drauliquid DOT 5.1** | **Drauliquid-LV Super DOT 4** | **Drauliquid-S DOT 4** |

*Change every 12 months*

## HYDRAULIC CLUTCH SYSTEM
Capacity: 0-0 liter (Between min and max.)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Drauliquid DOT 5.1** | **Drauliquid-LV Super DOT 4** | **Drauliquid-S DOT 4** |

*Change every 12 months*

## COOLING SYSTEM
Capacity: 1,2 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Coolant -38 Organic NF** | | |

## FRONT FORK WP 4860 MXMA CC
Capacity: 195 CM3 (cartridge each), Capacity: 390-400 CM3 (each leg without cartridge)

We are unable to give a standard recommendation for this component. Please contact our service department.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# KTM 450 450 SX-F (2013-2015)

## SHOCK ABSORBER REAR WP 5018 BAVP DCC

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367