

**KTM 450 450 XC-W (USA) (2012-2012)****ENGINE/TRANSMISSION**

Capacity: 1,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-50***Change every 10 hours/ 70 liter consumed fuel*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-50***Change every 1 hours/ 7 liter consumed fuel***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 5.1**

PRODUCT RECOMMENDATION 2

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 3

**Drauliquid-S DOT 4***Change every 12 months***COOLING SYSTEM**

Capacity: 1,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

PRODUCT RECOMMENDATION 2

**Coolant -26****FRONT FORK**

Capacity: 618 CM3 (each leg)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Fork Oil RR 5****SHOCK ABSORBER REAR**

We are unable to give a standard recommendation for this component. Please contact our service department.

# KTM 450 450 XC-W (USA) (2012-2012)



*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*