KTM 450 450 XC-W (2007-2011)



ENGINE/TRANSMISSION Capacity: 1,25 liter				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1				
Expulsa RR 5W-50				
Change every 15 hours/ 100 liter consumed fuel/ 1 race				
USE		CLIMATE		
Normal		Arctic		
PRODUCT RECOMMENDATION 1				
Expulsa RR 5W-40				
Change every 15 hours/ 100 liter consume	ed fuel/ 1 race			
USE		CLIMATE		
Initial service		Mediterranean		
PRODUCT RECOMMENDATION 1				
Expulsa RR 5W-50				
Change every 3 hours/20 liter consumed	fuel			
USE		CLIMATE		
Initial service		Arctic		
PRODUCT RECOMMENDATION 1				
Expulsa RR 5W-40				
Change every 3 hours/ 20 liter consumed fuel				
HYDRAULIC BRAKE SYSTEM				
Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Drauliquid DOT 5.1				

HYDRAULIC CLUTCH SYSTEM Brembo Capacity: 0-0 liter (Between min and max.)				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
Drauliquid DOT 5.1				
Change every 12 months				

Change every 12 months

KTM 450 450 XC-W (2007-2011)



HYDRAULIC CLUTCH SYSTEM Magura Capacity: 0-0 liter (Between min and max.)

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM Capacity: 1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

FRONT FORK Capacity: 0,57 liter (Total)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Fork Oil RR 5		
Change every 12 months	'	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.