

KTM 625 625 SXC (2002-2003)**ENGINE/TRANSMISSION**

Capacity: 1,6 liter

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

Expulsa RR 15W-50*Change every 2500 km/ 12 months/ 25 hours/ 1 race*

| USE | CLIMATE |
|--------|---------|
| Normal | Arctic |

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-50

PRODUCT RECOMMENDATION 2

Expulsa RR 10W-40*Change every 2500 km/ 12 months/ 25 hours/ 1 race*

| USE | CLIMATE |
|-----------------|---------------|
| Initial service | Mediterranean |

PRODUCT RECOMMENDATION 1

Expulsa RR 15W-50*Change every 1000 km/ 10 hours*

| USE | CLIMATE |
|-----------------|---------|
| Initial service | Arctic |

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-50

PRODUCT RECOMMENDATION 2

Expulsa RR 10W-40*Change every 1000 km/ 10 hours***HYDRAULIC BRAKE SYSTEM**

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Check every 5000 km, change every 12 months*

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Check every 1000 km*

KTM 625 625 SXC (2002-2003)**COOLING SYSTEM**

Capacity: 1 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

FRONT FORK

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Fork Oil RR 5 | | |

Change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.