

**ENGINE CR 65**

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Tornado**

## PRODUCT RECOMMENDATION 2

**Maestrol****TRANSMISSION 6**

Capacity: 0,3 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Drauliquid DOT 5.1**

*Check every 20 hours, change every 12 months*

**HYDRAULIC CLUTCH SYSTEM Brembo**

Capacity: 0-0 liter (Between min and max.)

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Drauliquid DOT 5.1**

*Check every 20 hours, change every 12 months*

**HYDRAULIC CLUTCH SYSTEM Magura**

We are unable to give a standard recommendation for this component. Please contact our service department.

**COOLING SYSTEM**

Capacity: 0,55 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

## PRODUCT RECOMMENDATION 2

**Coolant -26**

*Check every 20 hours, change every 12 months*

**KTM 65 / 85 / 105 SX 65 SX (2003-2008)****FRONT FORK**

Capacity: 0,21 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		

---

*Check every 20 hours, change every 12 months*


---

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*