KTM FREERIDE FREERIDE 350 (2015-2015)



ENGINE/TRANSMISSION Capacity: 1,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Expulsa RR 5W-50	
Change every 20 hours	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Expulsa RR 5W-50	
Change every 1 hours	

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min an	d max.)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid DOT 5.1	Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4
Change every 12 months	-	

HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and ma	ıx.)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid DOT 5.1	Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4
Change every 12 months		

COOLING SYSTEM Capacity: 0,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Check every 20 hours	,

FRONT FORK WP 4357 MXMA Capacity: 410 CM3 (each leg)

We are unable to give a standard recommendation for this component. Please contact our service department.

PRODUCT RECOMMENDATION

KTM FREERIDE FREERIDE 350 (2015-2015)



SHOCK ABSORBER REAR WP 4618 PDS DCC

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.