

KYMCO AGILITY AGILITY CITY 50 (2007-2016)



ENGINE

Capacity: 0,8 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 10W-40*Check every 1000 km, change every 2000 km*

USE

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 10W-40*Change every 300 km*

FINAL REDUCTION

Capacity: 0,2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 5000 km*

USE

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 300 km*

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Check every 1000 km, change every 10000 km/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.