LYNX RAVE RAVE RE 800 E-TEC (2014-2015)



ENGINE + AUTOMATIC LUBRICATION Rotax 800R

Capacity: 3,7 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

| HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and m | ax.) | | |
|---|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | | |

Check every 12 months, change every 6000 km/24 months

| COOLING SYSTEM Capacity: 0-0 liter (Between min and max.) | | | |
|---|----------|--|--|
| USE | CLIMATE | | |
| Normal | Moderate | | |
| PRODUCT RECOMMENDATION 1 | | | |
| Coolant -38 Organic NF | | | |

Check every 12 months, change every 60 months

CHAINCASE

Capacity: 0-0 liter (Between min and max.)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.