

MALAGUTI CENTRO CENTRO 125 I.E. (2007-2009)

**ENGINE KY-ML12**

Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 10W-40*Change every 4000 km/ 12 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 10W-40*Change every 1000 km***FINAL REDUCTION**

Capacity: 150 CM3

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 10W-40*Change every 12000 km*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 10W-40*Change every 1000 km***HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Change every 12000 km/ 24 months*

MALAGUTI CENTRO CENTRO 125 I.E. (2007-2009)



COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 4000 km/ 12 months, change every 24 months

FRONT FORK

Capacity: 90 CM3 (each leg)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Fork Oil RR 10		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.