## **MALAGUTI SPIDERMAX SPIDERMAX RS500**



(2009-2011)

ENGINE Piaggio M34CM Twin Spark Capacity: 1,7 liter (Dry fill), Capacity: 1,5 liter (Service fill)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Expulsa RR 5W-40			
Check every 5000 km/ 6 months, change every 10000 months/ 12 hours			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1			
Expulsa RR 5W-40			
Change every 1000 km			

FINAL REDUCTION Capacity: 0,25 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 10000 km/ 12 months.	change every 20000 months/ 24 hours	

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change avenuation less	'	

Change every 1000 km

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Check every 5000 km/ 6 months, change every 20000 months/ 24 hours			

## MALAGUTI SPIDERMAX SPIDERMAX RS500 (2009-2011)



COOLING SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		
Check every 5000 km/ 6 months, change every 20000 months/ 24 hours		

FRONT FORK Capacity: 385 CM3 (each leg)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Fork Oil RR 10	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.