## **MBK DOODO DOODO XN 125** (2000-2003)



ENGINE Capacity: 1,4 liter (Dry fill), Capacity: 1,2 liter (Service fill)			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Expulsa RR 15W-50	Expulsa RR 10W-40	Expulsa 10W-40	
Change every 6000 km/ 12 months			
USE		CLIMATE	
Initial service		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Expulsa RR 15W-50	Expulsa RR 10W-40	Expulsa 10W-40	

HUB REDUCTIONS REAR Capacity: 0,15 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Expulsa RR 10W-40	HDX 10W-40	
Expulsa RR 10W-40	HDX 10W-40	

Check every 6000 km, change every 12000 km

01 5001	·	·
Expulsa RR 10W-40	HDX 10W-40	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Initial service		Moderate
USE		CLIMATE

Change every 500 km

Change every 500 km

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3		
Change every 24 months	- 1	,		

## MBK DOODO DOODO XN 125 (2000-2003)



COOLING SYSTEM Capacity: 1,1 liter, Capacity: 0,35 liter (Reservoir)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Check every 6000 km/ 12 months, change every 36 months	

FRONT FORK Capacity: 125 CM3 (each leg)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.