## **MOTO GUZZI NTX 750 NTX, XPA** (1991-2001)



ENGINE Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Expulsa RR 10W-40	Expulsa 10W-40	

Change every 3000 km/ 12 months

SHAFT DRIVE Capacity: 0,16 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube GL-5 85W-140	
Check every 3000 km, change every 9000 km	'

TRANSMISSION 5/1
Capacity: 1 liter

USE CLIMATE
Normal Moderate

PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Check every 3000 km, change every 9000 km

Gearlube GL-5 80W-90

HYDRAULIC BRAKE SYSTEM				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			

Check every 3000 km, change every 15000 km

FRONT FORK Capacity: 0,46 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Change every 21000 km	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

## PRODUCT RECOMMENDATION

## **MOTO GUZZI NTX 750 NTX, XPA** (1991-2001)



information contained herein is subject to changes without notification.