

MOTORHISPANIA FURIA FURIA SM 50 (2003-2012)



ENGINE + AUTOMATIC LUBRICATION Minarelli AM6

Capacity: 1,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Tornado	Scoosynth	Maestrol

GEARBOX 6

Capacity: 0,75 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Expulsa RR 10W-40	HDX 10W-40	

Change every 10000 km

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Expulsa RR 10W-40	HDX 10W-40	

Change every 5000 km

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Expulsa RR 10W-40	HDX 10W-40	

Change every 500 km/ 3 months

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Change every 12 months

COOLING SYSTEM

Capacity: 0,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

MOTORHISPANIA FURIA FURIA SM 50 (2003-2012)

**FRONT FORK**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Perlus H 46

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.