## **MZ/MUZ 660 SKORPION TRAVELLER 660** (1996-2004)



| ENGINE/TRANSMISSION<br>Capacity: 2,6 liter, Filter capacity: 0 | ,1 liter                 |                          |
|--|--------------------------|--------------------------|
| use<br>Normal  |                          | climate<br>Mediterranean |
|  |                          |                          |
| Expulsa RR 15W-50  | HDX 15W-40               | HDX 20W-50               |
| Change every 6000 km/ 6 months                                 |                          |                          |
| USE  |                          | CLIMATE                  |
| Normal   |                          | Cold                     |
| PRODUCT RECOMMENDATION 1                                       | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Expulsa RR 10W-40  | Expulsa 10W-40           | HDX 10W-40               |
| Change over 6000 km/6 months                                   | I                        | 1                        |

Change every 6000 km/ 6 months

|                          | CLIMATE  |                          |
|--------------------------|----------|--------------------------|
|                          | Moderate |                          |
| PRODUCT RECOMMENDATION 2 |          |                          |
| Drauliquid-S DOT 4       |          |                          |
|                          |          | PRODUCT RECOMMENDATION 2 |

Check every 6000 km, change every 24 months

| COOLING SYSTEM<br>Capacity: 1,5 liter |                          |          |  |  |
|---------------------------------------|--------------------------|----------|--|--|
| USE                                   |                          | CLIMATE  |  |  |
| Normal                                |                          | Moderate |  |  |
| PRODUCT RECOMMENDATION 1              | PRODUCT RECOMMENDATION 2 |          |  |  |
| Coolant -38 Organic NF                | Coolant -26              |          |  |  |
|                                       |                          |          |  |  |

Check every 6000 km, change every 24 months

| FRONT FORK<br>Capacity: 0,22 liter                    |  |          |  |  |
|---|--|----------|--|--|
| USE   |  | CLIMATE  |  |  |
| Normal  |  | Moderate |  |  |
| PRODUCT RECOMMENDATION 1                              |  |          |  |  |
| Fork Oil RR 10  |  |          |  |  |
| Check every 6000 km, change every 12000 km/ 12 months |  |          |  |  |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.