

NORTON COMMANDER COMMANDER (1988-1992)



ENGINE

Capacity: 4,45 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

HDX 40

PRODUCT RECOMMENDATION 2

HDX 30*Check every 10000 km/ 3 months*

PRIMARY CHAINDRIVE

Capacity: 0,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 15W-50

PRODUCT RECOMMENDATION 2

HDX 20W-50*Check every 10000 km/ 3 months, change every 20000 km/ 12 months*

TRANSMISSION 5/1

Capacity: 0,95 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC BRAKE SYSTEM

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Check every 10000 km/ 3 months, change every 20000 km/ 12 months*

COOLING SYSTEM

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26*Check every 10000 km/ 3 months, change every 24 months*

NORTON COMMANDER COMMANDER (1988-1992)



FRONT FORK

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Fork Oil RR 10		

Change every 20000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.