OSSA TR TR 125I (2015-2015)



ENGINE + AUTOMATIC LUBRICATION				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Tornado	Scoosynth	Maestrol		

TRANSMISSION MANUAL 6 Capacity: 0,45 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
SP Gear 1081	SP Gear 5015			
Check every 30 hours, change every 60 hours				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
SP Gear 1081	SP Gear 5015			
Change every 5 hours				
USE		CLIMATE		
Second change only		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
SP Gear 1081	SP Gear 5015			

Change every 12 hours

COOLING SYSTEM Capacity: 0-0 liter ('max' capacity)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 11	
Change every 12 hours	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.