PGO I'ME / LIBRA I'ME / LIBRA 125 BF-125 (2008 AND AFTER)



ENGINE Capacity: 1 liter (Dry fill), Capacity: 0,8 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Expulsa RR 10W-40	HDX 15W-40			
Change every 1000 km				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Expulsa RR 10W-40	HDX 15W-40			
Change every 300 km/ 1 months				

HUB REDUCTIONS

Capacity: 0,11 liter (Dry fill), Capacity: 0,09 liter (Service fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Drauliquid DOT 3			
Change every 24 months			

FRONT FORK	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.