PIAGGIO FLY FLY 100 4T (2007-2014)



ENGINE Capacity: 0,85 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Expulsa RR 5W-40	
Change every 6000 km	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Expulsa RR 5W-40	
Check every 1000 km	

HUB REDUCTIONS REAR Capacity: 0,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 6000 km. change ever	v 24000 km	

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 1000 km	'	

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and m	nax.)		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

Check every 6000 km, change every 24 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Check every 1000 km		·

PIAGGIO FLY FLY 100 4T (2007-2014)



FRONT FORK Capacity: 0,02 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Check every 12000 km	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.