POLARIS HAWKEYE HAWKEYE 4X4 (2007-2008)



ENGINE ES300PFE010 Capacity: 1,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-50		
Change every 1000 miles/ 100 hours/ 6 me	onths	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-50		
Change every 200 miles/ 1 months/ 20 hou	urs	

DIFFERENTIAL FRONT

Capacity: 0,15 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION CVT 1

Capacity: 0,45 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Change avery 2000 miles/24 menths/	200 hours			

Change every 2000 miles/ 24 months/ 200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.