

# POLARIS PHOENIX PHOENIX 200 (2012 AND AFTER)



## ENGINE

Capacity: 1,2 liter

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-50***Change every 1000 miles/ 100 hours/ 6 months*

### USE

Initial service

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-50***Change every 250 miles/ 1 months/ 20 hours*

## DIFFERENTIAL REAR

Capacity: 0,12 liter

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

### PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90***Change every 1000 miles/ 12 months/ 100 hours*

## TRANSMISSION CVT 1/1

Capacity: 0,55 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

## HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

### PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4***Change every 2000 miles/ 24 months/ 200 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.