POLARIS SCRAMBLER SCRAMBLER 850 XP (EPS) (2014-2014)



ENGINE EHO850LE Capacity: 1,9 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Expulsa RR 5W-50			
Change every 1000 miles/ 100 hours/ 6 months			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1			
Expulsa RR 5W-50			
Change every 250 miles/ 1 months/ 25 hours			

DIFFERENTIAL FRONT

Capacity: 0,28 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL REAR Capacity: 0,21 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90			
Change every 1000 miles/ 12 months/ 100 hours				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90			

Check every 250 miles/ 1 months/ 25 hours

TRANSMISSION CVT 1/1

Capacity: 1,1 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

POLARIS SCRAMBLER SCRAMBLER 850 XP (EPS) (2014-2014)



HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

Change every 2000 miles/ 24 months/ 200 hours

COOLING SYSTEM Capacity: 1,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 24 months	·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.