

POLARIS SPORTSMAN 6X6 SPORTSMAN BIG BOSS 6X6 800 EFI (2011-2013)

**ENGINE EH076OLE**

Capacity: 1,9 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-50*Change every 1000 km/ 6 months/ 100 hours*

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-50*Change every 200 km/ 1 months/ 20 hours***DIFFERENTIAL FRONT**

Capacity: 0,28 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL MIDDLE

Capacity: 0,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 12 months***DIFFERENTIAL REAR**

Capacity: 0,15 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Change every 12 months***TRANSMISSION CVT 1/1**

Capacity: 0,45 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC SYSTEM ACTIVE DESCENT CONTROL (ADC)

Capacity: 0-0 liter (Between min and max.)

We are unable to give a standard recommendation for this component. Please contact our service department.

POLARIS SPORTSMAN 6X6 SPORTSMAN BIG BOSS 6X6 800 EFI (2011-2013)



HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

| USE | | CLIMATE |
|----------------------------------|---------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |

Change every 2000 km/ 24 months/ 200 hours

COOLING SYSTEM

Capacity: 3,4 liter

| USE | | CLIMATE |
|-------------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant -38 Organic NF | | |

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.